



Material	High-quality all aluminum, surface hard anodized
Processor	Onboard Intel Celeron J6412(quad core four threads, 2.0GHz,Max to 2.6GHz)
CPU structure	Elkhart Lake
Memory	Support 1*DDR4 3200MHz SODIMM, Max 32 GB
BIOS	AMI UEFI BIOS
Chipset	Intel(R) UHD Graphics
Display Port	1*HDMI, 2*DP(Support Synchronous/asynchronous triple display, Resolution Max 4096x2160 @ 60Hz)
Front I/O	1*Power switch, 3*USB3.1, 3*USB2.0, 1*COM , 1*SIM card slot
Rear I/O	1*DC, 2*DP, 1*HDMI, 3*2.5G Lans, 1*Audio (Support Mic and Speaker at the same time)
Expansion Slot	Support 1*M.2 2280 M-key slot (support SATA protocol)
	Support 1*M.2 3052 B-key slot (USB3.0 signal, support 4G/5G), 1*SIM slot
	Support 1*M.2 2230 E-key slot (support WIFI, Bluetooth)
Network	3*Intel i225-V 2.5G LAN
Storage	1*M.2 2280 slot, 1*2.5 inch HDD/SSD
Power Supply	DC 12V input
Work Temp	Power-on, Timed power-on, network wake-up, PXE boot, watchdog (level 0-255), TPM2.0 security encryption
Work Temp	- 0℃ ~ +40℃(Commercial HDD), -20℃ ~ +60℃(Industrial SSD),Surface air flow
Work Humidity	0% ~ 95% non-condensing
Dimension	150 * 126.5 * 45 mm
Weight	0.84 kg